



HX5.EX-1.4P.3000.C 4 Pallet Scale, HX5.EX-1.4P.1500.C 4 Pallet Scale, HX5.EX-1.4P.600.C 4 Pallet Scale

More information on the website
radwag.com/en/info,w1,JVD



HX5.EX-1.4P.3000.C 4 Pallet Scale
HX5.EX-1.4P.1500.C 4 Pallet Scale
HX5.EX-1.4P.600.C 4 Pallet Scale

The drawings, photos and graphics used are for illustrative purposes only.

Functions



Labelling



Plus/Minus Control



Percent Weighing



Parts counting



Newton unit measurement



Statistics



GLP Procedures



Replaceable unit



ALIBI Memory

Datasheet

	HX5.EX-1.4P.600.C 4 Pallet Scale	HX5.EX-1.4P.1500.C 4 Pallet Scale	HX5.EX-1.4P.3000.C 4 Pallet Scale
Metrological parameters			
Maximum capacity [Max]	600 kg	1500 kg	3000 kg
Minimum load	4 kg	10 kg	20 kg
Readability [d]	200 g	500 g	1000 g
Tare range	-600 kg	-1500 kg	-3000 kg
Max readability for non-verified scale		500 g	
OIML Class	III	III	III
Physical parameters			
Display	5" graphic colour	5" graphic colour	5" graphic colour
Weighing pan dimensions	840×1200 mm	840×1200 mm	840×1200 mm
Packaging dimensions	1400×900×430 mm	1400×900×430 mm	1400×900×430 mm
Net weight	49,8 kg	49,8 kg	49,8 kg
Gross weight	50 kg	50 kg	50 kg
Communication interface			
Communication interface	2×RS232, RS485	2×RS232, RS485	2×RS232, RS485
Electrical parameters			
Power supply	100 – 240 V AC 50/60 Hz	100 – 240 V AC 50/60 Hz	100 – 240 V AC 50/60 Hz
Power consumption max.	15 W	15 W	15 W
Environmental conditions			
Operating temperature	-10 ÷ +40 °C	-10 ÷ +40 °C	-10 ÷ +40 °C
Construction			
Construction	mild steel St3S	mild steel St3S	mild steel St3S



Extra payment for verification



Accessories

Communication Modules
 Ex-Scale-Intended Intrinsically Safe Power Supply for PUE HX5.EX
 Weighing Terminal

Receipt Printer

Software

RAD-KEY
 R-LAB
 E2R System

LabVIEW Driver
 RADWAG Development Studio
 R.Barcode