

KERN VHB 2T1

KERN

Pallet truck scale with complete protection against dust and water splashes
IP65/67 and a memory for a container weight



Kategorie

Brand	KERN
Product category	Industrial scale
Product group	Pallet truck scale
Product family	VHB

Measuring System

Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	2000 kg
Readability [d]	1 kg
Resolution	2.000
Linearity	± 2 kg
Reproducibility	1 kg
Default unit	kg
Units	kg lb

Adjustment options	Adjusting with external weight
Recommended adjusting weight	1500 kg (M2)
Stabilization time	3 s
Warm-up time	10 min
Eccentric loading at 1/3 [Max]	3 kg
Eccentric/Off-centre loading is not possible	✓
Maximum creep (15 minutes)	2 kg
Maximum creep (30 minutes)	4 kg

Approval

CE mark	✓
---------	---

Display

Display type	LCD
Display digit height	28 mm
Languages of the user interface	Symbol language

Construction

Dimensions completely mounted (W×D×H)	1550×555×1220 mm
Material display housing	Plastics
Material housing	plastic

Functions

Auto-off interval(s) in battery mode/rechargeable battery mode	3 min
PreTare function	✓
Tare function	manual (multi)
Recipe/summing level	Sum A
Underfloor weighing	None
IP protection - complete device	IP65 IP67 (load cell)
IP protection - display	IP65
IP protection - load cell	IP67
IP protection - platform	IP67

Power Supply

Supplied power supply	Battery
Battery	4× 1.5 V AA
Battery / accumulator type	Alkali(-Manganese)
Battery connection	Pad + Spring
Battery voltage	6 V
Battery operating time	80 h

Environmental conditions

Humidity of environment [Max]	95 %
Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	40 °C

Packing & Shipping

Readability force [d] (N)	2 d
Shipping method	Freight
Dimensions packaging (W×D×H)	1600×560×1220 mm
Net weight approx.	110 kg
Gross weight approx.	110 kg
Shipping weight	218,6 kg

KERN VHB 2T1



Pallet truck scale with complete protection against dust and water splashes IP65/67 and a memory for a container weight

Services (optional)

Article number for DAkkS calibration	963-131
Article number for adjustment at the location of installation	961-251
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD



OPTION

